Carmen® Box – add ANPR+MMR data to any (existing) camera



MAKE & MODEL RESULTS:					
MAKE:	0	AUDI	app		
MODEL:	0	A8	Auði		
COLOR:	0	GRAY			
CATEGORY:	0	CAR			

DIRECTION:


APPROACHING



148.6(W)


Interface

Input stream (one stream / Carmen® BOX)	Camera stream protocols: RTSP		
	Camera stream format: H.264		
	Supported resolution: up to 5MP		
Output stream	The output stream is the same as the input stream (no transcoding)		
Output formats	HTTP/HTTPS/FTP/SFTP upload		
	Data stream through API		
	Internal database on web interface		
	GDS upload		
Output data	Device ID		
	ANPR data: Number plate data in UNICODE text, Location of each plate on one image, Country/State		
	MMR data (make, model, color), Vechicle direction / Lane information (certain camera position)		
	Time stamps		
	JPEG event image, Background color, Character color, Category of the plate		
Data storage requirements	1000 – 2000 events 8 GB storage (included), 4-8 MB per event		
	50 000 – 100 000 events require 512 GB storage (optional)		
GUI	Running on any standard browser, easy to adjust		
Trigger	Multiple trigger options: Triggerless, Software-based, Hardware-based		
Connected applications	Globessey Data Server (GDS); Middleware for data management (incl. statistics) from multiple Carmen® BOX, Enforce BOX, and other devices (license required).		
	Harbard Discovery Tool: Essential detection tool for identifying the IP addresses of Carmen® BOX and Enforce BOX devices in a network. Suitable for license updates and uploads for multiple devices.		




General Information

ANPR Engine	On-Board Carmen® ANPR+MMR
Engine update availability	Included: 1 year from purchase
	Optional: Subscription available on a yearly basis
Hardware key (NNC)	Built-in mini-PCle card
Platform	NVIDIA® Jetson NanoTM's GPU-accelerated
Connectivity	LAN x2 (1 pcs PoE 15 W)
Storage options	8 GB microSD card included, user-changeable up to 512 GB
	external USB3 drives (not included) can also be added
Data storage requirements	8 GB storage for 1000-2000 events included, 4-8MB per event
	512 GB storage for 50-100.000 events could be optionally added
Electrical Data	



Power requirement	12V 5A DC (60W); 100-240V/50-60Hz power supply with EU plug included		
Power consumption typical	15 W (without POE power up)		
Mechanical Data			
Internal operating temperature	-30°C - +60°C (-22°F - +140°F)		
Dimensions without wall mounting kit (LxWxH)	129.8 x 148.6 x 34.6 mm (5.11" x 5.85" x 1.36")		
Weight	1 kg (2.20 lb)		

Carmen® Box device, power supply (12V 5A), wall mounting kit



Certificates

Certificate CE, FCC Class A

In the box



www.adaptiverecognition.com